

# Product Specifications For P13.5-6

<b>Minimum Rating</b>	12.5 kVA / 10 kW
<b>Maximum Rating</b>	16.5 kVA / 13.2 kW
<b>Emissions/Fuel Strategy</b>	EU3a Emissions Compliant
<b>50 Hz Prime</b>	12.5 kVA / 10 kW
<b>50 Hz Standby</b>	13.5 kVA / 10.8 kW
<b>60 Hz Prime</b>	15 kVA / 12 kW
<b>60 Hz Standby</b>	16.5 kVA / 13.2 kW
<b>Frequency</b>	50 / 60 Hz
<b>Speed</b>	1500 or 1800 RPM
<b>Voltage</b>	220-415 Volts
<b>50 Hz Prime Rating</b>	These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.
<b>60 Hz Prime Rating</b>	These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528-3).
<b>50 Hz Standby Rating</b>	Standard reference conditions 25°C (77°F) Air Inlet Temp, 100m (328 ft) A.S.L. 30% relative humidity. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, Class A2.

<b>Engine Model</b>	Perkins® 403D-15G
<b>Bore</b>	84 mm (3.3 in)
<b>Stroke</b>	90 mm (3.5 in)
<b>Governor Type</b>	Electronic
<b>Displacement</b>	4.4l (268.5 cu. in)
<b>Compression Ratio</b>	18.3:1

## P13.5-6 Standard Equipment

### Engine

Air Cleaner

Lube oil drain valve

Engine filled with lubrication oil

High Coolant Temperature Shutdown

Low Oil Pressure Shutdown

### Cooling

Package mounted radiator

Radiator & Cooling Fan

Coolant Drain Valve

Fan, Fan drive and battery charging Alternator drive fully guarded to meet EC Machinery Directive

Cooling System filled with Coolant mix

### Exhaust

Exhaust flange outlet

Exhaust stub pipe and gasket

### Fuel

8 Hr Fuel Tank or Skidbase

Fuel Fittings for Local and Remote Feed

### Alternator

FG Wilson Alternator

SHUNT Excitation

IP23 Protection

### Control Panel

FG100

### Mounting

Base, Formed Steel with Skid base or Single wall Fuel Tank

Certified Base Mounted Lifting Eyes, and Rear Drag Eyelets

Anti-vibration mounts

Battery Tray and Cables

## **P13.5-6 Optional Equipment**

### **Exhaust**

Industrial, Residential, Critical Silencers

### **Alternator**

Leroy Somer Alternator

Quadrature Droop Kit

Anti-Condensation Heater and Panel Circuitry

Anti-Condensation Heater and Panel Circuitry

### **Control Panels**

DSE4520

DSE7320

DSE7410

Deep Sea DSE7420

### **Starting/Charging**

Lead Acid battery (Dry)

### **General**

Upgrade to Standard Set for "CE" Certification

EEC Declaration of Conformity

Narrow, Wide or Skid Base

Sound attenuated, steel or galvanised enclosure

Dual wall fuel tanks

### **Enclosure**

Compliance to European Community Directive 2000/14/EC

Super sound attenuation for residential areas

Totally enclosed exhaust silencing system

Robust and highly corrosion resistant construction