

Product Specifications For P500-3

Minimum Rating	455 kVA / 364 kW
Maximum Rating	500 kVA / 400 kW
Emissions/Fuel Strategy	Fuel Optimised
50 Hz Prime	455 kVA / 364 kW
50 Hz Standby	500 kVA / 400 kW
Frequency	50 Hz
Speed	1500 RPM
Voltage	220-415 Volts
Engine Model	Perkins® 2506A-E15TAG1
Bore	137 mm (5.4 in)
Stroke	171.0mm (6.7 in)
Governor Type	Electronic
Displacement	15.2l (927.6 cu. in)
Compression Ratio	16.0:1

P500-3 Standard Equipment

Engine

Air Cleaner

Lube oil drain valve

Engine filled with lubrication oil

High Coolant Temperature Shutdown

Low Oil Pressure Shutdown

Engine mounted battery charging alternator

Cooling

Package mounted radiator

Radiator fan and charging alternator guards

Coolant Drain Valve

Cooling System filled with Coolant mix

Exhaust

Exhaust flange outlet

Exhaust bellows and gasket

Fuel

8 Hr Fuel Tank

BSP Fuel Sockets

Alternator

FG Wilson

SHUNT Excitation

IP21 Protection

Control Panel

PowerWizard 1.1+

Mounting

Robust steel constructed base frame

Base frame drag and lift points

Captive linear vibration isolators between base and engine-generator

Battery Tray and Cables

P500-3 Optional Equipment

Exhaust

Industrial, Residential, Critical Silencers

Alternator

Quadrature Droop Kit (AR6)

Anti-Condensation Heater and Panel Circuitry (AH1)

AREP / PMG excitation

AVR Upgrades

Three phase sensing

Oversize Alternator

Coastal ingress protection alternator

Leroy Somer

Control Panels

PowerWizard 2.1

easYgen-2500

Starting/Charging

Heavy duty dry battery

Battery charger with auto boost

General

Upgrade to Standard Set for "CE" Certification

EEC Declaration of Conformity

Dual wall base tank (8 hrs)

Sound attenuated or High ambient enclosures

Battery isolator switch

Enclosure

Compliance to European Community Directive 2000/14/EC

Super sound attenuation for residential areas

Totally enclosed exhaust silencing system

50°C High ambient capability available

Robust and highly corrosion resistant construction